

Technical Data	Audi e-tron GT quattro 350 kW
Program for Germany	Status: 02/19/2021
Engine / electrics	
Peak electrical output boost in kW	390
Peak electrical output in kW	350
Continuous electrical output in kW	140
Electrical torque output boost in Nm (<i>lb-ft</i>)	640 (472.0)
Electrical torque output in Nm (<i>lb-ft</i>)	630 (464.7)
Battery type	Lithium-ion
Battery capacity gross / net in kWh	93.4 / 83.7
Battery in A / Ah	380 / 40
Max. electrical output at 12V in kilowatts	3
On-board voltage 1 in volts	12
On-board voltage 3 in volts	800
Drivetrain / transmission	
Drive type	All-wheel drive
Transmission type	2-speed / automatic
Suspension / steering / brakes	
Type and design of front-axle suspension	Double-wishbone suspension
Type and design of rear-axle suspension	Multi-link suspension
Steering	Electromechanical steering with speed-dependent power assistance
Steering ratio	15.4
Turning circle in m (<i>ft</i>)	11.6 (38.1)
Brake control system	Dual-circuit brake system with black/white split for front/rear axles; ESC/ABS/EBD; brake booster, hydraulic brake assist
Tires (basic) front rear	225/55 R 19 275/45 R 19
Wheels (basic) front rear	Alloy 8 J x 19" 10 J x 19"
Performance / acoustics	
Top speed in km/h (<i>mph</i>)	245 (152.2)
Limited	yes
Electrical acceleration, 0-100 km/h (<i>62.1 mph</i>) in s	4.5
Electrical acceleration boost, 0-100 km/h (<i>0-62.1 mph</i>) in s	4.1
Exterior noise level when stationary / drive-past as per ECE R51.03 in dB (A)	- / 69
Consumption / range	
Electric power consumption, combined, in kWh/100 km (<i>62.1 mi</i>) *	19.6 - 18.8 (NEDC); 21,6 - 19,9 (WLTP)
CO2 emissions, combined, in g/km (<i>g/mi</i>)	0
Electrical range, combined according to WLTP in km (<i>mi</i>) *	488 - 452 (303.2 - 280.9)
Servicing / guarantee (Germany)	
Service interval	30,000 km (<i>18,641.1 mi</i>) / 2 years, whichever comes first
Vehicle / paint / rust perforation guarantee	2 / 3 / 12 (years)
Insurance classification in Germany: third party / fully comprehensive / part-comprehensive	20 / 29 / 28

Weights / loads	
Unladen weight without driver / with driver / gross weight limit in kg (<i>lb</i>)	2276 (5017.7) / 2351 (5183.1) / 2840 (6261.1)
Front/rear axle load limit in kg (<i>lb</i>)	1395 (3075.4) / -
Roof load limit / permissible nose weight in kg (<i>lb</i>)	75 (165.3) / -
Capacities	
Cooling system capacity (incl. heating) in l (<i>US gal</i>)	18.9 (5.0)
Dimensions / body	
Body type / number of doors	Unitary steel/aluminum composite construction / 4
Number of seats	5
Drag coefficient Cd / frontal area A in m ² (<i>sq ft</i>)	0.24 / 2.35 (25.3)
Standard dimensions (length / width excluding mirrors / height with steel springs / height with air springs) in mm (<i>ft</i>)	4989 (16.4) / 1964 (6.4) / 1413 (4.64) / 1396 (4.58)
Width including mirrors in mm (<i>ft</i>)	2158 (7.1)
Wheelbase / track width front/rear in mm (<i>ft</i>)	2900 (9.5) / 1710 (5.6) / 1694 (5.6)
Overhang angle of steel springs, front/rear in degrees	16.00 / 12.00
Overhang angle of air spring front/rear in degrees	13.0 / 16.4
Height of loading edge with steel springs / air springs in mm (<i>ft</i>)	697 (2.3) / 681 (2.2)
Closed luggage compartment - behind the 2nd seat row in l (<i>cu ft</i>)	405 (14.3)

* Figures depend on the equipment selected.