

Technical Data		Audi RS e-tron GT 440 kW	
Program for Germany		Status: 02/04/2021	
Engine / electrics			
Peak electrical output boost in kW		475	
Peak electrical output in kW		440	
Continuous electrical output in kW		142	
Electrical torque output boost in Nm (<i>lb-ft</i>)		830 (612.2)	
Electrical torque output in Nm (<i>lb-ft</i>)		830 (612.2)	
Battery type		Lithium-ion	
Battery energy content in kWh		93.4	
Battery in A / Ah		380 / 40	
Max. electrical output at 12V in kilowatts		3	
On-board voltage 1 in volts		12	
On-board voltage 3 in volts		800	
Drivetrain / transmission			
Drive type		All-wheel drive	
Type of rear axle differential		Controlled axle-differential lock	
Transmission type		2-speed / automatic	
Suspension / steering / brakes			
Type and design of front-axle suspension		Double-wishbone suspension	
Type and design of rear-axle suspension		Multi-link suspension	
Steering		Electromechanical steering with speed-dependent power assistance	
Steering ratio		15.4	
Turning circle in m (<i>ft</i>)		11.6 (38.1)	
Brake control system		Dual-circuit brake system with black/white split for front/rear axles; ESC/ABS/EBD; brake booster, hydraulic brake assist	
Tires (basic) front rear		245/45 R 20 285/40 R 20	
Wheels (basic)		Alloy 9 J x 20" 11 J x 20"	
Performance / acoustics			
Top speed in km/h (<i>mph</i>)		250 (155.3)	
Limited		yes	
Electrical acceleration, 0-100 km/h (<i>62.1 mph</i>) in s		3.6	
Electrical acceleration boost, 0-100 km/h (<i>0-62.1 mph</i>) in s		3.3	
Exterior noise level when stationary / drive-past as per ECE R51.03 in dB (A)		- / 68	
Consumption / range			
Electric power consumption, combined, in kWh/100 km (<i>62.1 mi</i>)*		20.2 - 19.3 (NEDC); 22.5 - 20.6 (WLTP)	
CO2 emissions, combined, in g/km (<i>g/mi</i>)		0	
Electrical range, combined according to WLTP in km (<i>mi</i>)*		472 - 433 (293.3 - 269.1)	
Servicing / guarantee (Germany)			
Service interval		30,000 km (<i>18,641.1 mi</i>) / 2 years, whichever comes first	
Vehicle / paint / rust perforation guarantee		2 / 3 / 12 (years)	
Insurance classification in Germany: third party / fully comprehensive / part-comprehensive		20 / 30 / 28	

Weights / loads	
Unladen weight without driver / with driver / gross weight limit in kg (<i>lb</i>)	2347 (5174.2) / 2422 (5339.6) / 2860 (6305.2)
Front/rear axle load limit in kg (<i>lb</i>)	1385 (3053.4) / -
Roof load limit / permissible nose weight in kg (<i>lb</i>)	75 (165.3) / -
Capacities	
Cooling system capacity (incl. heating) in l (<i>US gal</i>)	18.9 (5.0)
Dimensions / body	
Body type / number of doors	Unitary steel/aluminum composite construction / 4
Number of seats	5
Drag coefficient Cd / frontal area A in m ² (<i>sq ft</i>)	0.24 / 2.35 (25.3)
Standard dimensions (length / width excluding mirrors / height with steel springs / height with air springs) in mm (<i>ft</i>)	4989 (16.4) / 1964 (6.4) / - / 1396 (4.6)
Width including mirrors in mm (<i>ft</i>)	2158 (7.1)
Wheelbase / track width front/rear in mm (<i>ft</i>)	2900 (9.5) / 1702 (5.6) / 1667 (5.5)
Overhang angle of steel springs, front/rear in degrees	10.80 / 12.70
Overhang angle of air spring front/rear in degrees	13.0 / 16.4
Height of loading edge with steel springs / air springs in mm (<i>ft</i>)	- / 681 (2.2)
Closed luggage compartment - behind the 2nd seat row in l (<i>cu ft</i>)	350 (12.4)

* Figures depend on the equipment selected.